

**PROSPAN LVL15 TRIMMING STUDS**



**Prolam**<sup>®</sup>

Engineered Laminated Timber

Single, upper or lower of two storeys Up to  
HIGH WIND ZONE

**TOP FIXINGS PER STUD:**

**3.15 dia nails or 12g type 17 screws**

Minimum fixing 4 nails or 2 screws

Lintel Span	Trimming Stud size	No of trimming studs	No of Nails	No of Screws	Alternative fixing
<b>Stud height (m) 2.4</b>					
3.6	90x45	1	4	2	
3.9	90x45	1	5	2	
4.2	90x45	1	5	2	
4.5	90x45	1	5	2	
4.8	90x45	1	5	2	
5.1	90x45	1	6	3	CPC40 plus 2 nails
5.4	90x45	1	6	3	CPC40 plus 2 nails
6.0	90x45	2	5	2	CPC40
6.6	90x45	2	5	3	CPC40 + 1 nail
7.2	90x45	2	9	3	CPC40 + 2 nails
7.8	90x45	2	9	3	CPC40 + 2 nails
8.4	90x45	2	7	3	CPC40 + 2 nails
<b>Stud height (m) 2.7</b>					
3.6	90x45	2	4	2	
3.9	90x45	2	4	2	
4.2	90x45	2	4	2	
4.5	90x45	2	4	2	
4.8	90x45	2	4	2	
5.1	90x45	2	4	2	
5.4	90x45	2	4	2	
6.0	90x45	3	4	2	
6.6	90x45	4	4	2	
7.2	90x45	4	4	2	
7.8	90x45	4	4	2	
8.4	90x45	4	4	2	